

### Versatile Enexxis 1080P Outdoor Bullet Camera

The Enexxis XX-B1-1080 Outdoor Bullet Camera features high-resolution 1080p technology, vandal-resistant design, and built-in 3-9mm Varifocal Lens. Designed for exterior use where high-resolution video surveillance is required. Equipped with a true day/night cut filter, this camera provides excellent image quality in extreme lighting conditions, making it an excellent choice for demanding 24x7 surveillance applications.



#### KEY FEATURES

- » 1080p HD Resolution
- » 3-9mm or 3.3-12mm varifocal lens
- » ProSet feature lets you zoom and focus directly from your PC (1080p & 720p)
- » Dual streaming video
- » DPC (Defective Pixel Correction) on select models
- » External alarm I/O
- » Setup and recording software included
- » 42 IR LEDs provide over 100' illumination range
- » IP66 rated for all weather performance
- » Mounting bracket and sunshield included
- » Built-in fan and heater

MODEL	XX-ED1-1080P-IR-6MM
Image Sensor	1/2.8" Progressive Scan CMOS
Max. Resolution	1080p
White Balance	ATW / Manual (Preset)
Digital Zoom	2 - 10x (Client Software)
Shutter Speed	1/4, 1/10, 1/12.5, 1/15, 1/20, 1/25, 1/30, 1/50, 1/60, 1/100, 1/120, 1/480, 1/960, 1/1024, 1/2000 sec
Day/Night Performance	IR Cut Filter, True Day/Night
Dynamic Range	50 dB
IR Illumination	42 IR LEDs
Other Functions	DPC (Defective Pixel Correction) AGC, BLC, Mirror/ Flip
<b>Lens</b>	
Typical/Focal Length	3-9mm Varifocal with P-Iris
Max. Aperture	F1.2
Iris	Motorized Iris / AES / Manual
ProSet Remote Zoom/Focus	Yes
<b>Analog</b>	
Video Signal	NTSC / PAL Selectable
Monitor Output	Composit output (BNC), 75 ohm 1Vpp
Audio In/Out	Line in, Line out (external amplifier needed)
<b>Network</b>	
Network	10BASE-T, 100BASE-TX, RJ45
Image Compression	H.264, MJPEG - (2nd stream only)
Resolution	1920 x 1080 (Full HD), 1280 x 1024 (SXGA), 1280 x 720 (720p), 640 x 480
Protocol	IPv4, HTTP, SMTP, UPnP, DNS, RTP, TCP, UDP, RTCP, DHCP, ARP, IGMP, ICMP, NTP / IPv6
Frame Rate	1 fps ~ 30 fps
Web Browser	Internet Explorer 7.0 or above, Firefox, Chrome, PDA / Smart phone
Security	Password Protection, HTTPS, IP Addressing Filtering
SDK (API)	HTML based API - ONVIF
VMD - Video Motion Detection	User set 4 ROI (Region of Interest), 10 Step Sensitivity
Alarm Trigger	VMD, External Alarm Input
Alarm Event	E-mail notification (Snapshot), FTP transfer (Snapshot), SD Card (Snapshot),
<b>Power</b>	
24VAC	4.8W / Max 9.6W (IR / P-iris / Fan on)
PoE	Class 0 (IEEE 802.3af compliant)
<b>Other Specifications</b>	
MicroSD Card	MicroSDHC card compatible - SanDisk, Transcend, Kingston, Toshiba: 1G, 2G, 4G, 8G, 16G or more
External I/O Terminals	Alarm In x1, Alarm Out x1, Audio In x1, Audio Out x1
Operating Temperature/RH	14°F ~ 122°F (-10°C ~ 50°C) / With Heater -40°F ~ 122°F (-40°C ~ 50°C)
Weight	4.1 lbs. / 1.9kg
Dimensions	Camera & bracket -11.7"L x 3.3" Ø
Weather Rating	IP66
Certifications	ONVIF Profile S, CE, FCC, WEEE
Additional	Built in Fan and Heater