

### Midrange and Versatile 3-Bay Tower Access Control Server

The XX-B-PRO4-AC-TWR meets the highest industry standards and can handle the 24/7 security demands of smaller-scale access control systems.

The Intel® Core™ 8th generation processor manages multiple concurrent processor-intensive tasks with capacity to spare.

Throughput optimized solid state drives (SSD) provide fast startup and application load times.

Maintain peace of mind and lower the total cost of ownership with a five-year, next business day, on-site, Keep Your Hard Drive warranty.

### KEY FEATURES

- Intel® Core™ i7-8700k Processor
- PCIe NVMe OS Solid State Drive
- Operating System: Windows 10 Pro



 I/O Performance Optimized



SSD Drives



5-Year, On-site, NBD,  
Keep Your Hard Drive Warranty



Intel® Core™ i7 Processor



Back

— POWERED BY —  
**DELL EMC**

**FOR MORE INFORMATION:** [enexxis.com](http://enexxis.com) | [info@enexxis.com](mailto:info@enexxis.com) | +1.215.322.8400

Copyright © 2019, Enexxis. All rights reserved. This document is provided for information purposes only. The contents are subject to change without notice.

SYSTEM	
<b>Processor(s)</b>	Intel® Core™ i7-8700k 8th Generation Processor (6 Cores, 12 Threads, 3.70GHz)
<b>Processor Passmark</b>	Intel® Core™ i7-8700k: 15,963
<b>Operating System</b>	Windows 10 Pro
<b>Operating System Drives</b>	(2) 960GB SSD
<b>Memory</b>	Standard Configuration: 16GB (2x 8GB DDR4) (4x DDR4 DIMM Slots)
<b>Networking</b>	(1) 1GbE RJ45 Port
<b>USB(s)</b>	Rear (4) USB 3.0, (2) USB 2.0; Front (1) USB 3.0; (2) USB 2.0, (1) USB 3.1 Type-C
<b>Expansion Slots</b>	Standard Configuration: (1) PCIe x16 full-height, (2) PCIe x4 full-height, (1) PCI
<b>Graphics</b>	NVIDIA® Quadro® P400
<b>Video Outputs</b>	(1) DisplayPort (1) HDMI
<b>Manufacturer</b>	Enexxis
<b>Warranty</b>	5-Year, On-site, NBD, Keep Your Hard Drive Warranty
MECHANICAL	
<b>Form Factor</b>	Tower
<b>Hard Drive Bays</b>	(3) 3.5" Bays, (1) M.2 SSD Slot
<b>Hard Drives Supported</b>	SSD & SATA
<b>Power Supply(s)</b>	(1) 460W   100-240VAC
<b>Maximum Power Draw</b>	460W
<b>Operating Temperature</b>	(Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35° C]
<b>Operating Humidity</b>	5 ~ 90% (non-condensing)
<b>Dimensions (WxDxH)</b>	6.95" x 17.66" x 13.03" (176.6mm x 345mm x 331mm)
<b>Max. Weight</b>	23.37 lbs (10.6 kg)



**FOR MORE INFORMATION:** [enexxis.com](http://enexxis.com) | [info@enexxis.com](mailto:info@enexxis.com) | +1.215.322.8400

Copyright © 2019, Enexxis. All rights reserved. This document is provided for information purposes only. The contents are subject to change without notice.